

FC-420

FUTURA™ COMMANDO

- Z 80900 ROLL UP FLOOR
- Z 80901 ROLL UP FLOOR SHORT SHAFT
- Z 80902 RIGID FLOOR
- Z 80903 RIGID FLOOR SHORT SHAFT



COMBAT TESTED

The FC range is well known throughout the world as the definitive inflatable raiding craft. The FC range is used by more elite soldiers and sailors than any other craft worldwide. It is the standard by which other raiding craft are judged.

This success is a result of its unique patented hull shape, and the choice of accessories and floor systems that together offer adaptability for a wide range of missions.

The patented Futura Commando hull shape allows unsurpassed maneuverability and increased ability to plane with heavy loads.



CAPACITY

. maximum number of persons (ISO6185) :	6	6
. maximum payload (ISO6185) :	870 kg	1918 lb
. floorboard usable area :	2.154 m ²	23.19 ft ²
. buoyancy tube volume :	1.32 m ³	47 ft ³

DIMENSIONS

. overall length :	4.20 m	13' 9"
. inside length :	2.80 m	9' 2"
. overall width :	1.75 m	5' 9"
. inside width :	0.84 m	2' 9"
. weight empty :	120 kg	265 lb
. buoyancy tube diameter :	0.45 m	1' 6"
. folded dimensions :	0.65 x 1.40 m ² 2' 2" x 4' 7"	

FABRIC

Duratane® CSM / Neoprene Fabric

- . main buoyancy tube : black . 1100 dtx, polyamide
- . keel buoyancy tube : black , 1100 dtx, polyamide
- . FUTURA™ tubes : black , 1100 dtx, polyamide
- . bottom : black , 1100 dtx, polyamide

ENGINE POWER

. shaft length :	Long	20"
. recommended power :	25 hp	19 kW
. maximum power :	30 hp	23 kW
. maximum engine weight :	75 kg	165 lb

SAFETY / INFLATION

. airtight compartments on main tube :	3
. inflatable keel :	1
. FUTURA™ tubes :	2
. design category (EC 94/25) :	C
. Fast inflation included as standard?	NO

FLOOR

- . roll-up floorboards (aluminum slats) : 1

VALVES

- . intercommunication / inflation valves on main tube : 2
- . keel inflation valve : 1
- . fast inflation points : 2
- . overpressure valves : 2
- . connecting hoses from main tube to FUTURA™ tubes : 2

TRANSOM BLACK

- . self-bailers large flow with scuppers : 2
- . aluminum engine mounting plate (single engine) : 1
- . transom sacrificial plate (marine plywood) : 1
- . tension straps transom / floorboard : 1

REINFORCEMENTS

- . peripheral rubbing strake, flat profile, black : 1
- . flat rubbing strake underneath keel, black : 1
- . flat rubbing strake underneath FUTURA™ tubes, black : 1+1
- . anti-splash triangles : 2
- . transom bottom stainless steel protection shoe : 1

TOWING AND LIFTING

- . D rings : stainless steel with black coating
- . bow large towing D rings : 2
- . aft large towing D rings : 2
- . bow large lifting D rings : 2
- . aft lifting points in transom : 2

HANDLING

- . lateral carrying handles (straps + hose) : 6
- . bow carrying handle : 1
(metal with black coating)
- . exterior lifeline (peripheral) : 1
- . interior lifeline : 2
- . interior large tie down D rings : 9

OTHER EQUIPMENT

- . foot pump : 2
- . cylinder attachment sleeve on roll-up floor : 1
- . repair kit (including pressure indicator) : 1
- . paddles (aluminum shaft, plastic blade) : 4
- . bow pouch (removable) : 2
- . boat carrying bag : 1

ACCESSORIES

- Lifting Sling
- Bow Towing bridle
- Aft Towing bridle
- Fast inflation kit Air
- Keel auto inflation kit
- Dive bottle 15L
- Watertight engine bag
- ECOPE
- BOAT HOOK
- 10kg anchor package w/ line
- Boat overall cover
- Mooring line Black
- Fuel tank strap

FC-420 RU